

PAT-NO: JP359105509A
DOCUMENT-IDENTIFIER: JP 59105509 A
TITLE: USED AMOUNT DETECTOR FOR
WELDING WIRE
PUBN-DATE: June 18, 1984

INVENTOR-INFORMATION:

NAME	COUNTRY
HIRAMATSU, MASAKI	

ASSIGNEE-INFORMATION:

NAME	COUNTRY
MITSUBISHI ELECTRIC CORP	N/A

APPL-NO: JP57216226
APPL-DATE: December 9, 1982

INT-CL (IPC): G01B021/06, G01B007/04

US-CL-CURRENT: 324/76.11

ABSTRACT:

PURPOSE: To stabilize welding accurately and positively capturing residue by detecting used amount of a welding wire from revolutions of a winding frame.

CONSTITUTION: A pulse generator 26 outputs a pulse signal each time a detector 24 detects a projection 22, where the cycle T1 is the time for

one rotation of a winding frame 60. A timer circuit 28 starts to measure time by a synchronous signal of the generator 26 and completes the operation of a time piece after the set time T2 of a variable time setting device 30. A time comparator 32 compares the cycle T1 and the time T2 and a welding wire 12 is continuously pulled out when $T1 > T2$. When the relation turns to $T1 \leq T2$, a signal of the circuit 32 activates an alarm circuits 34 to forcibly stop a motor 16 and alarming or the like is performed with a buzzer. The time T2 can be adjusted freely with the setting device 30 while the residue of the wire 12 for actuating a circuit 34 can be set as desired thereby accurate and positive sensing of the residue and the used amount of the wire 12 can be performed.

COPYRIGHT: (C)1984, JPO&Japio